

SPEKTRA Anti Mould

USE

The biocide water-based preparation as an additive to interior and facade dispersion paint for the preventive protection of the painted wall surfaces against the growth of different types of mould and algae. It prevents the growth of microorganisms on the already attacked surfaces.

CHARACTERISTICS

- Long-term fungicide and algacide protection of the coloured wall surfaces
- Additive to different water based wall paints
- Water based

TECHNICAL DATA

PRODUCT TYPE	fungicide/algacide preparation in water
COLOUR SHADES	white, not transparent liquid
TINTING	/
DENSITY	1,0 kg/l
THINNING	/
PACKAGING	1 l
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5 °C to +35 °C, in dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE!

INSTRUCTIONS FOR USE

APPLICATION	mixing into dispersion paint
WORKING CONDITIONS	min. +5 °C air, surface and paint.
COVERAGE	Shake the product well and add it to the paint in a quantity 10 %.
CLEANING OF TOOLS	Immediately after use with water.

SURFACE PREPARATION

The surface should be free from dust, crumbly particles and other impurities. Remove old falling off coats. Fill up bigger cracks and damaged surface with adequate materials on the mineral basis. Afterwards impregnate with an appropriate impregnation. Prior to painting, the surface should be dry and firm. Apply **SPEKTRA Sanitol** to interior/exterior surfaces, which are attacked by mould and algae. After the surfaces have dried, remove mould mechanically. Add **SPEKTRA Anti Mould** to the chosen paint, thus preventing for a longer period the growth of microorganisms. Paint the spots of nicotine, water outflow, tar, waterproof pencils... with **SPEKTRA antinicotine paint**, which already represents the final coating. Remove saltpetre with brushing and impregnate surface with **SPEKTRA deep impregnation**. Clean crack-free »healthy« surfaces, which are painted with smooth, gloss or semi-gloss enamels or dispersion paints and sand them with the sanding paper (No. 150).

COATING SYSTEMS

The procedure for the preparation of surface, impregnation, puttying and painting is stated in technical information of the chosen dispersion paint, to which we add **SPEKTRA Anti Mould**.

REMARKS

- Mix **SPEKTRA Anti Mould** thoroughly before its addition to the paint. The selected dispersion paint should be mixed as well.
- Add **SPEKTRA Anti Mould** into the paint during mixing (e.g. with an electric mixer).
- For the efficient biocide protection, we recommend applying two coats of paint, to which you added **SPEKTRA Anti Mould**.
- Do not mix **SPEKTRA Anti Mould** with biocide preparations of other producers.
- Store out of reach of children.
- Do not empty into a sewage system.
- Use the suitable protection gloves.
- Use biocides safely. Always read the label and product information before use.