

SPEKTRA DOMFLOK flakes

USE

The pigmented dry flakes in multi-colour decorative system **SPEKTRA DOMFLOK** for the decoration of the interior wall surfaces in the corridors, halls, waiting rooms, staircases in the public and residential buildings. They are suitable for the combination in the colourless **SPEKTRA DOMFLOK lacquer gloss, semi-matt or matt**.

CHARACTERISTICS

- Numerous colour combinations
- Vivid appearance of interior wall surfaces

TECHNICAL DATA

PRODUCT TYPE	acrylic pigmented flakes
COLOUR SHADES	colour chart SPEKTRA DOMFLOK
PACKAGING	50 g
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE!

INSTRUCTIONS FOR USE

APPLICATION	brush (flakes mixed into SPEKTRA DOMFLOK lacquer)
WORKING CONDITIONS	min. +5 °C air, surface and paint
DRYING (T= +20 °C, rel hum. 65%)	the coating is dry and suitable for overcoating after 4 – 6 hours
COVERAGE	50 - 75 g in 1 l of SPEKTRA DOMFLOK lacquer
CLEANING OF TOOLS	immediately after use with water

SURFACE PREPARATION

The surface, which is painted with the selected basic dispersion paint (washability class min. 2 (EN 13300)), which must be suitably dry for the lacquer application.

COATING SYSTEMS

SURFACE	TOP COAT
2x SPEKTRA latex matt	1x SPEKTRA DOMFLOK lacquer gloss, semi-matt or matt with the mixed in SPEKTRA DOMFLOK flakes

APPLICATION TECHNIQUE

Apply **SPEKTRA DOMFLOK lacquer** with the mixed in flakes with a brush in criss-cross technique. After 1 m² of the applied lacquer roll over the surface with wet short hair mohair roller in upside-down direction to remove brush traces. Remove the excess of lacquer from the roller with spatula. If you return the excess lacquer back to the pail, it has to be considered that the concentration of flakes in the mixture will be reduced.

REMARKS

- At first mix the chosen **SPEKTRA DOMFLOK flakes** of different colour shades dry, afterwards mix them with a wooden bar into **SPEKTRA DOMFLOK lacquer**.
- Mix the flakes into the lacquer immediately before the application. We do not recommend a longer storage of the already prepared mixture of flakes and the lacquer.
- We combine the flakes colours with the selected colour of the surface.