

# SPEKTRA Fresh&Easy

## AREA OF APPLICATION

For the protection and decoration of wall and ceiling surfaces. The paint contains micro-encapsulated fragrance that is released into the space over a long time, enriching it with a fresh scent. The duration of the fragrance release depends on the ambient temperature and ventilation.

It is suitable for painting all types of mineral plasters, fibre-cement panels, concrete, plaster-cardboard panels, wallpapers made of glass fibres, paper relief wall papers and old coatings

## PROPERTIES

- contains micro-encapsulated jasmine fragrance
- excellent hiding power already with the first layer
- warm white shade
- high vapour permeability
- health- and environmentally friendly

## TECHNICAL DATA

COMPOSITION	vinylacetate copolymer dispersion, pigments, fillers and special additives
COLOUR SHADES	white
GLOSS (EN 13300)	matt
DENSITY	1.61 – 1.65 kg/l
WASHABILITY (EN 13300)	Class 5 (not washable)
WATER VAPOUR PERMEABILITY $s_d$ (ISO EN 7783-2:2012)	0,014 ± 0,006 (class V <sub>1</sub> , high water vapour permeability)
THINNING	with water up to 10 %
EU VOC category and limits	IIA(a), 140 g/l (2010); the product contains: max. 10 g/l
PACKAGING UNITS	5 l, 14 l
SHELF LIFE	The shelf life of an originally sealed and suitably stored product (temperature ranging from 5 °C to 35 °C, in a dry place) is indicated on the packaging. DO NOT FREEZE!

## INSTRUCTIONS FOR USE

APPLICATION METHOD	roller, brush, spraying
WORKING CONDITIONS	the paint, air and surface temperature should be at least +5 °C.
DRYING (T= +20 °C, rel. humidity 65 %)	dry and suitable for subsequent application after 4– 6 hours.
COVERAGE	Theoretically: approx. 8 - 12 m <sup>2</sup> with 1 l and one application Actual consumption depends on the absorbency and roughness of the surface.
CLEANING TOOLS	with detergent, immediately after use

## SUBSTRATE PREPARATION

The surface should be free from dust, loose particles and other impurities. Remove any loose old coats. Fill up large cracks and damaged parts of the surface with adequate mineral-based materials. Then impregnate with **SPEKTRA acrylic impregnation**. Prior to painting, the surface should be dry and firm.

Apply **SPEKTRA biocide agent SANITOL** to wall surfaces affected by mould or algae. Once the walls are dry, remove the mold mechanically. To **SPEKTRA interior wall paint Fresh&Easy**, add **SPEKTRA protection against mould ZP**, which will prevent the growth of microorganisms for a long time.

Cover nicotine, water leakage, tar, waterproof pencil and other spots with **SPEKTRA antinicotine paint**, which is used as the final coating. Clean crack-free, healthy surfaces painted with smooth, gloss or semi-gloss enamels or dispersion paints, and sand them with sandpaper (No. 150).

## COATING SYSTEMS

SURFACE	SUBSTRATE PREPARATION	IMPREGNATION	SMOOTHING	TOP COAT
<b>New uncoated surfaces</b> - lime-cement plasters - plaster-cardboard plates  - concrete and other non-porous substrates		1x <b>SPEKTRA acrylic</b> impregnation  1x <b>SPEKTRA deep</b> impregnation	2x <b>SPEKTRA interior putty</b> - fine (if necessary)	1 - 2x <b>SPEKTRA Fresh&amp;Easy</b>
<b>Painted with dispersion paints</b> - several layers of permeable, not washable coatings  - smooth, glossy, washable coatings	cleaning, removal of loose particles, repair of damaged areas  cleaning, sanding	1x <b>SPEKTRA acrylic</b> impregnation		

## NOTES AND SPECIAL FEATURES

- Mix well before use.
- Drying time increases at lower temperatures and higher air humidity.
- If thinned with water in higher quantities than recommended, the hiding power of the paint film proportionally decreases.