

SPEKTRA Stain Block Grund

AREA OF APPLICATION

A water-based primer designed to block water-soluble stains. Excellent at blocking stains from nicotine, soot, water spills, tannins, wine, juices, coffee, colored pencils, markers, etc., and prevents their appearance after the application of the finishing coat. Any SPEKTRA brand dispersion wall paint is suitable as a finishing coat. Intended for indoor and outdoor use.

CHARACTERISTICS

- excellent blocking of water-soluble stains
- easy to apply
- health- and environmentally friendly
- almost odorless

TECHNICAL DATA

COMPOSITION	Styrene-acrylic dispersion, fillers, and special additives.
COLOUR SHADES	semi-transparent
TINTING	not tintable
GLOSS (EN 13300)	semi-matt
DENSITY	1.0 – 1.1 kg/l
THINNING	not to be thinned
EU VOC category and limits	IIA(h), 30 g/l (2010); the product contains: max. 10 g/l
PACKAGING UNITS	2 l / 5 l
SHELF LIFE	The shelf life of an originally sealed and suitably stored product (temperature ranging from +5°C to +35°C, in a dry place) is indicated on the packaging. MUST NOT FREEZE!

INSTRUCTIONS FOR USE

APPLICATION METHOD	roller, brush, spraying
WORKING CONDITIONS	the paint, air and surface temperature should be at least +5°C.
DRYING (T = +20°C, rel. humidity 65%)	dry and suitable for subsequent application after 24 hours.
COVERAGE	Theoretically: up to 30 m ² with 1 l and one application The actual consumption depends on the absorbency and roughness of the surface.
CLEANING TOOLS	with water, immediately after use

SURFACE PREPARATION

The surface should be free from dust, loose particles and other impurities. Prior to painting, the surface should be dry and firm. Apply **SPEKTRA biocide agent SANITOL** to wall surfaces affected by mold or algae. Once the walls are dry, remove the mold mechanically. **SPEKTRA Anti Mould** is added to the finishing coat, which prevents the growth of microorganisms for a longer period. Before applying the finishing coat, prepare the surface according to the instructions specified in the technical information of the selected coat.

COATING SYSTEMS

SURFACE	SURFACE PREPARATION	PRIMER	TOP COAT
Painted with dispersion paints - several layers of permeable, not washable coatings - smooth, glossy, washable coatings	Cleaning, removal of unbound particles	1x SPEKTRA Stain Block Grund	2x SPEKTRA interior or facade paint

NOTES AND SPECIAL FEATURES

- Mix **SPEKTRA Stain Block Grund** well before use.
- The drying time increases at lower temperatures and higher air humidity.
- **SPEKTRA Stain Block Grund** perfectly blocks water-soluble stains, but does not cover them. The stains are covered by the finish coat.
- Do not sand **SPEKTRA Stain Block Grund** before applying the finishing coat.