



Consider the recommended thinning of the wall paint, as paint that is too thin will worsen the coating's coverage.

Drying time of the coating depends on the temperature and humidity in the room. It is significantly longer at lower temperatures or high humidity; and shorter at higher temperatures, which can in turn cause the uneven appearance of the dry coating. We recommend painting under normal air conditions.

After applying the first coat of paint, cover the roller tightly with kitchen foil to prevent the paint on the roller from drying out. When you have finished painting, wash the tool immediately under cold water with a few drops of dishwasher detergent. Then rinse the roller thoroughly under clean water. To remove any excess water, intensively rotate the roller handle.

WISE TIPS

Follow us on:  Helios TBLUS



Kitchen & Bathroom

Wall paint with mold prevention function



Helios TBLUS d.o.o.
Količevo 65, 1230 Domžale, Slovenia
T +386 1 722 40 00
E deco.coatings@helios.si
www.helios-deco.com
Member of HELIOS.

For a balanced home

SPEKTRA Kitchen & Bathroom is an interior wall paint that prevents mold growth for a long time. It is particularly suited to rooms such as kitchens, bathrooms, utility rooms, drying rooms and all rooms where an increased amount of steam can cause the development of harmful microorganisms. The coating is highly vapour-permeable, has good hiding power and a pleasant smell of pine tree during application and drying.

The paint is suitable for painting all types of mineral plasters, fibre-cement panels, plaster-cardboard panels, concrete and old coatings.

- high level of vapour permeability
- slows down the formation of condensation
- easy application



• PLEASANT SMELL



• BIOCIDAL PROTECTION OF THE COATING



Use

The surface should be free from dust, loose particles, grease and other impurities. Remove old, flaking coatings. Fill up large cracks and damaged parts of the surface with adequate mineral-based materials. Impregnate with **SPEKTRA acrylic impregnation**. Prior to painting, the surface should be dry and firm. Then apply **SPEKTRA Kitchen & Bathroom**, which should be mixed well before use and if required, thinned with water to a maximum of 10 %. Application with a roller, brush or spraying. To achieve the best results, we recommend applying two coats. The interlayer coating time is 4–6 hours. 1 l covers 8–12 m² of smooth wall surface in one coat.

Coating system

IMPREGNATION	LEVELLING	FINISHING COAT
1 × SPEKTRA acrylic impregnation	2 × SPEKTRA LEVEL FINE (as required)	2 × SPEKTRA Kitchen & Bathroom



Classification (EN 13 300)

- Gloss level:** matt
- Washability:** class 4
- Hiding power:** superb