


HELIOS**TESSAROL®**
HELIOS**TESSAROL®**

For long-term durability as well as more intensive whiteness, more coats in thinner layers are to be applied (up to 70 microns of wet film) in recommended intervals. Air drying requires as good as possible weather conditions (10–25 °C, relative humidity under 75 %).

**WISE
TIPS**

Follow us on:  Helios TBLUS


HELIOS

Helios TBLUS d.o.o.
Količevo 65, 1230 Domžale, Slovenia
T +386 1 722 40 00
E deco.coatings@helios.si
www.helios-deco.com
Member of KANSAI HELIOS.

TESSAROL PRO PROTECT

Quick-drying top coat

Quick drying top coat
TESSAROL PRO PROTECT

is used for protection and decoration of metal, wooden and plastic surfaces in indoor and outdoor spaces. The coating offers excellent hiding power in a single coat already. With the use of a universal primer, it offers excellent anti-corrosion protection and excellent protection against all weather conditions. The shades are light-durable thanks to their persistent pigments. The coating is ideal for completely changing the appearance of metal and wooden surfaces; windows, doors, fittings, wood claddings, fences, constructions, furniture and other metal and wood indoor surfaces and surfaces in less exposed outdoor areas.



WHERE DO WE USE IT?

The product is suitable for application on surfaces including: windows, doors, fittings, wood claddings, fences, constructions, furniture and other metal and wood indoor surfaces and surfaces in less exposed outdoor areas.

INSTRUCTIONS FOR USE

TESSAROL PRO PROTECT is applied onto a surface that is first protected with the **TESSAROL universal primer UNI**. We recommend one coat of primer, followed by 2 coats of top coat.

The surface must be dry, sanded and cleaned. Mix the coating well before use.

- Up to 10 years of UV protection
- Stable gloss and stable colour shade (white and light shades practically do not become yellow)
- Excellent hiding power
- Quick drying – next coat in just 6 hours
- Easy to apply, easy to work with, good levelling
- Good elasticity and hardness
- Great weather resistance
- Resistance to household cleaning agents

APPLICATION: brush, roller, spraying

DRYING TIME: 6 hours before the next application, under normal conditions of 23 °C, rel. humidity: 50 %

NUMBER OF COATS: 2

THINNING: with **TESSAROL thinner** if necessary

CONSUMPTION: 1 l covers 14–16 m² of surface in 1 coat

PACKAGING UNITS: standard colour shades: 0.75 l
HGMIX: 0.75 l

COLOUR SHADES: 6 standard colour shades, that can be mixed with each other.

